

PROFESSIONAL PROTECTION FOR HARDWOOD FLOORS™

# TIE TACK

CLEANING SOLUTION



Use the following Tie Tack cleaning systems for periodic deep cleaning, and to reduce spreading contaminants during screen and recoats.

Periodic Cleaning	Clean before screening
<p>Mix three parts water to one part Tie Tack solution in a bucket and clean entire floor. If floor is heavily soiled, two cleanings may be required.</p>	<p>Use Tie Tack full strength before screening to reduce the risk of contaminants during the coating process.</p>

1. In bucket, mix the appropriate ratios of Tie Tack and water. Dip untreated cotton towels in solution and wring towels before placing flat on floor.
2. Place push broom on towel one foot from leading edge and fold leading edge over the top of push broom. Push towel the entire length of floor. Before returning back down the floor, lift and move push broom back on towel about six inches so that only a clean portion of the towel is on the leading edge, and fold the soiled portion of towel on top or behind the broom bristles. Repeat the process until there is not a clean edge on the towel. At that point turn the towel over and continue.
3. When towel becomes dirty or dry, replace with new clean towel. Never dip dirty towel in clean solution. Continue cleaning with fresh towels until entire floor is tacked. If floor still appears dirty it may be necessary to tack the floor again with the Tie Tack solution.