

Revision Date: 24-May-2018 Revision Number: 4

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name RAPID SEAL DUAL PURPOSE SEALER

Product Code 1Y-519
Alternate Product Code TR1119
Product Class SEALER
Color Clear

**Recommended use**Solvent-borne coatings **Restrictions on use**No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300 101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

Montvale, NJ 07645 Phone: 1-866-708-9180 lenmar-coatings.com

# 2. HAZARDS IDENTIFICATION

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

#### Label elements

# Danger

#### Hazard statements

Causes skin irritation

May cause an allergic skin reaction

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Revision Date: 24-May-2018



Appearance liquid Odor little or no odor

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

#### Skin

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded

#### Other information

No information available

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Stoddard solvent	8052-41-3	45
Distillates, petroleum, hydrotreated light	64742-47-8	20
Methyl ethyl ketoxime	96-29-7	0.5
Cobalt bis(2-ethylhexanoate)	136-52-7	0.5

# 4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Keep eye wide open while

Revision Date: 24-May-2018

rinsing. If symptoms persist, call a physician.

**Skin Contact** Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation persists, call a physician. Wash

clothing before reuse. Destroy contaminated articles such as shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

If not breathing, give artificial respiration. Call a physician immediately.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Do not induce

vomiting without medical advice. Never give anything by mouth to an unconscious

person. Consult a physician.

**Protection Of First-Aiders**Use personal protective equipment.

Most Important Symptoms/Effects

May cause allergic skin reaction.

Notes To Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam, dry powder or water. Use extinguishing measures

that are appropriate to local circumstances and the

surrounding environment.

**Protective Equipment And Precautions For** 

**Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Combustible material. Closed containers may rupture if

exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and

vapors.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge Yes

**Flash Point Data** 

 Flash Point (°F)
 105.0

 Flash Point (°C)
 40.6

 Method
 PMCC

Flammability Limits In Air

Lower flammability limit:Not availableUpper flammability limit:Not available

NFPA Health: 1 Flammability: 2 Instability: 0 Special: Not Applicable

### NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions**Use personal protective equipment. Remove all sources of ignition.

**Other Information** Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be

Revision Date: 24-May-2018

advised if significant spillages cannot be contained.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

**Handling** Use only in area provided with appropriate exhaust ventilation. Do not breathe

vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from

open flames, hot surfaces and sources of ignition.

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away

from heat. Keep away from open flames, hot surfaces and sources of ignition.

Keep in properly labeled containers. Keep out of the reach of children.

**DANGER** - Rags, steel wool or waste soaked with this product may

spontaneously catch fire if improperly discarded. Immediately after use, place

rags, steel wool or waste in a sealed water-filled metal container.

**Incompatible Materials** Incompatible with strong acids and bases and strong oxidizing agents.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL
Stoddard solvent	100 ppm - TWA	500 ppm - TWA
		2900 mg/m³ - TWA

# Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

#### **Personal Protective Equipment**

**Eye/Face Protection** Safety glasses with side-shields.

**Skin Protection** Long sleeved clothing. Protective gloves.

Respiratory Protection In operations where exposure limits are exceeded, use a NIOSH approved

respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a

Revision Date: 24-May-2018

NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling. When using do not eat,

drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

 Density (lbs/gal)
 7.0 - 7.4

 Specific Gravity
 0.84 - 0.88

pH No information available

Viscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information available

 Wt. % Solids
 30 - 40

 Vol. % Solids
 25 - 35

 Wt. % Volatiles
 60 - 70

 Vol. % Volatiles
 65 - 75

 VOC Regulatory Limit (g/L)
 < 550</td>

Boiling Point (°F) 315
Boiling Point (°C) 157
Fracting Boint (°F) No inform

Freezing Point (°F)

Freezing Point (°C)

No information available
No information available

Flash Point (°F) 105.0 Flash Point (°C) 40.6

1Y-519 - RAPID SEAL DUAL PURPOSE SEALER

Method PMCC

Flammability (solid, gas) Not applicable

Upper flammability limit:

Lower flammability limit:

Autoignition Temperature (°F)

Autoignition Temperature (°C)

Decomposition Temperature (°F)

Decomposition Temperature (°C)

No information available

# 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions. Hazardous polymerisation

does not occur.

Conditions to avoid Keep away from open flames, hot surfaces, static

electricity and sources of ignition.

Revision Date: 24-May-2018

Incompatible Materials Incompatible with strong acids and bases and strong

oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating

gases and vapors.

Possibility of hazardous reactions None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

**Product Information** Repeated or prolonged exposure to organic solvents may lead to permanent brain

and nervous system damage. Intentional misuse by deliberately concentrating and

inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** Contact with eyes may cause irritation.

**Skin contact** May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the

skin and produce dermatitis.

**Ingestion** Ingestion may cause irritation to mucous membranes. Small amounts of this

product aspirated into the respiratory system during ingestion or vomiting may

cause mild to severe pulmonary injury, possibly progressing to death.

**Inhalation** High vapor / aerosol concentrations are irritating to the eyes, nose, throat and

lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and

Revision Date: 24-May-2018

other central nervous system effects.

**Sensitization** May cause an allergic skin reaction.

No information available. **Neurological Effects** No information available. **Mutagenic Effects** No information available. Reproductive Effects **Developmental Effects** No information available. Target organ effects No information available. STOT - repeated exposure No information available. STOT - single exposure No information available. Other adverse effects No information available.

**Aspiration Hazard** May be harmful if swallowed and enters airways. Small amounts of this product

aspirated into the respiratory system during ingestion or vomiting may cause mild

to severe pulmonary injury, possibly progressing to death.

#### Numerical measures of toxicity

# The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 26680 mg/kg ATEmix (dermal) 10672 mg/kg

## **Component Information**

#### **Acute Toxicity**

#### Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat) LD50 Dermal: > 3160 mg/kg (Rabbit) LC50 Inhalation (Vapor): > 6.1 mg/L (Rat) Distillates, petroleum, hydrofreated light

LD50 Oral: > 5,000 mg/kg (Rat) LD50 Dermal: > 3,000 mg/kg (Rabbit)

Methyl ethyl ketoxime LD50 Oral: 930 mg/kg (Rat) LD50 Dermal: 200 μL/kg (Rabbit)

LC50 Inhalation (Vapor): > 4.8 mg/L (Rat)

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Cobalt bis(2-ethylhexanoate)	Carcinogen		

• Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

## 12. ECOLOGICAL INFORMATION

Revision Date: 24-May-2018

# **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

## **Product Information**

#### **Acute Toxicity to Fish**

No information available

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

# **Acute Toxicity to Aquatic Plants**

No information available

# Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

## **Mobility in Environmental Media**

No information available.

#### **Ozone**

No information available

# **Component Information**

# **Acute Toxicity to Fish**

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

# **Acute Toxicity to Aquatic Invertebrates**

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

# **Acute Toxicity to Aquatic Plants**

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
Empty Container Warning	Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.
	14 TRANSPORT INFORMATION

# 14. TRANSPORT INFORMATION

Revision Date: 24-May-2018

#### DOT

**Proper Shipping Name PAINT** Hazard class UN-No. UN1263 **Packing Group** Ш

Description UN1263, PAINT, 3, III, Marine Pollutant (Stoddard solvent)

In the US this material may be reclassified as a Combustible Liquid and is not regulated in containers of less than 119 gallons (450 liters) via surface transportation (refer to 49CFR173.120(b)(2) for further information).

ICAO / IATA Contact the preparer for further information.

IMDG / IMO Contact the preparer for further information.

## 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States** Yes - All components are listed or exempt. Yes - All components are listed or exempt. **DSL: Canada** 

# Federal Regulations

## SARA 311/312 hazardous categorization

Acute health hazard Yes Chronic Health Hazard Yes Fire hazard Yes Sudden release of pressure hazard No Reactive Hazard No

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# **US State Regulations**

## **California Proposition 65**

WARNING: Cancer and Reproductive Harm— www.P65warnings.ca.gov

## State Right-to-Know

1Y-519 - RAPID SEAL DUAL PURPOSE SEALER

Revision Date: 24-May-2018

Chemical name	Massachusetts	New Jersey	Pennsylvania
Stoddard solvent	X	X	X
1,2,4-Trimethylbenzene	X	X	X

# Legend

X - Listed

# 16. OTHER INFORMATION

HMIS -Health: 1\* Flammability: 2 Reactivity: 0 PPE: -

## **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By **Product Stewardship Department** 

> Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 24-May-2018 Not available **Revision Summary** 

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**